

# Roll 1300

|                     |                           |
|---------------------|---------------------------|
| EXT DIM             | 1100 x 1100 x H 1930 mm   |
| INT DIM             | 900 x 910 x H 1570 mm     |
| INT VOLUME          | 1285 litres               |
| COEF.K              | 0,31 W/m2.K               |
| WEIGHT              | 156 Kg                    |
| INSULATING MATERIAL | Polyurethane foam         |
| WALL MATERIAL       | Food grade polyethylene   |
| SIZE                | EXT Asia pallet 1100x1100 |




## Specifications



Monobloc rotomoulding. Internal convection grooves




Double axles door hinge. Door opens to 270°



2-points «pelican» quick closing system, rustproof treated



Rustproof treated steel frame, flush mounted, 4 wheels Ø 125 mm, 2 fixed, 2 swivelling



EPDM one-piece frame seal. Door hold-open system



Embedded label holder



2 embedded moulded handles



Door hold-open system, half-height door



## Options



TOP 370 eutectic plate



Eutectic plate holder



Dry ice drawer



2 braked casters Ø 125 mm



4 metal feet Ø 80 mm



1 to 3 plastic coated steel shelves



1 to 3 stainless steel shelves



LEADER IN INSULATED CONTAINERS  
www.olivo.eu - Tel. +33 (0)4 77 90 68 63