




# BAC 160

## Information

OUTER DIMENSIONS	800 x 600 x H 1050 mm
INNER DIMENSIONS	580 x 370 x H 700 mm
INNER VOLUME	150 Litres
K COEFFICIENT	0,32 W/m2.K
CURB WEIGHT	51 kg
INSULATION	Polyurethane foam
WALLS	Food-graded polyethylene
OUTER SIZE	Half EUR pallet : 600x800mm



## Specifications



Chest and lid made of food-graded monobloc rotomolded polyethylene



Monobloc frame silicone seal



Embedded rustproof treated steel chassis




Embedded closing latch - sealable with a padlock/seal



4 wheels  $\varnothing$  125 mm: 2 fixed, 2 swivel or 4 metal feet  $\varnothing$ 80 mm.



4 molded handles



Inner convection groovings



Embedded label holder



Eutectic plate molded shelf



Lid fitted with metal bowls to enable stacking of BAC when on feet



Chest/lid molded hinge, 105° opening



Drain plug

## Accessories



Eutectic plate TOP 370



4 wheels  $\varnothing$  125 mm : 2 fixed and 2 swivel wheels with brakes




4 swivel wheels with 2 brakes  $\varnothing$  125 mm



Molded logo



Customized logo on marking plate



Several colors available under conditions on request